High Resolution Day & Night, WDR Zoom Camera

SCC-C4233/C4235 *NEW*
SCC-C4333/C4335

Features

- 1/4" 410K/470K pixels CCD
- 32x Optical zoom lens (16x D-zoom)
- High resolution Day & Night : 540(Color)/570(BW) TV Lines
- Minimum scene illumination :
  (SCC-C4233(P)/C4333(P) : 0.002 Lux (15 IRE, Sens-up 256x, Color)
                          : 0.0002 Lux (15 IRE, Sens-up 256x, B/W)
  SCC-C4235(P)/C4335(P) : 0.001 Lux (15 IRE, Sens-up 256x, Color)
                          : 0.0001 Lux (15 IRE, Sens-up 256x, B/W))
- Full auto focus function
- Privacy mask zone (16 area)
- Multi-protocol (more than 8 companies), multi-OSD
- Remote control(RS485), power zoom/focus control

## 512x Zoom (32x Optical, 16x Digital)

32x Optical Zoom Lens(f=3.55 ~ 113mm) / 16x Digital Zoom with DSP IC
Maximum 512x Zoom Function allows for easy identification of distant object.

512x Zoom

Dimensions (unit:mm)

SCC-C4233/4235

60.5 / 59.5 / 115.2 / 10

SCC-C4333/4335

60.5 / 59.5 / 149.2 / 10

Specifications

Model			SCC-C4233(P)	SCC-C4333(P)	SCC-C4235(P)	SCC-C4335(P)
Camera Type			Color			
Image	Device		1/4" Super-HAD IT CCD		1/4" Ex-View-HAD PS CCD	
	Effective Pixels	NTSC	768(H) x 494(V)			
		PAL	752(H) x 582(V)			
Minimum Scene Illumination	Color		0.6 Lux(15IRE,Sens-up Off)		0.3 Lux(15IRE,Sens-up Off)	
			0.002 Lux(15IRE, Sens-up x256)		0.001 Lux(15IRE, Sens-up x256)	
	B/W		0.06 Lux(15IRE,Sens-up Off)		0.03 Lux(15IRE,Sens-up Off)	
			0.0002 Lux(15IRE, Sens-up x256)		0.0001 Lux(15IRE, Sens-up x256)	
Functions	Number of Privacy Zone		16			
	Day & Night		Color/BW/Auto (Moving Filter)			
	Line Lock		N/A	INT/Line Lock	N/A	INT/Line Lock
	White Balance		ATW1/ATW2/AWC/MANUAL			
	D-Zoom		Yes (~16x)			
	High Speed Shutter		Yes (OFF ~ 1/10K)			
	Motion Detection		Yes			
	Sens Up		Yes (2x ~ 256x)			
	Camera ID		Max 20 Character			
	Remote Control		RS485, Power Zoom/Focus			
	Alarm	Input	N/A			
		Output	1			
	Wide Dynamic Range		N/A		Yes	
Horizontal Resolution			540(Color)/570(BW) TV Lines			
Video Output			VBS 1.0Vp-p			
S/N Ratio			About 50 dB			
Lens	Focal Length		3.55 ~ 113mm			
	Zoom Ratio		32x Optical			
	Aperture Ratio		F1.69(W)/F4.17(T)			
	Viewing Angle	Tele	1.78°(H) x 1.34°(V)			
		Wide	56.41°(H) x 43.01°(V)			
Operating Temperature			-10℃ ~ + 50℃			
Operating Humidity			Less than 90%			
Power	Power Requirement	NTSC	DC 12V	AC24V/DC12V,60Hz	DC12 V	AC24V/DC12V,60Hz
		PAL		AC24V/DC12V,50Hz		AC24V/DC12V,50Hz
	Power Consumption		4W	5W		5.5W
	LED Indicator		Yes			
Dimensions	Net(mm)		60.5 X 59.5 X 125.2	60.5 X 59.5 X 159.2	60.5 X 59.5 X 125.2	60.5 X 59.5 X 159.2
Weight	Net		444g	595g	444g	595g
Color	Body		Silver			